

VERSÁTIL, IMPERMEABLE Y COLORIDO

Star Plus

VERSATILE, WATERPROOF AND COLORFUL



Características del tejido | Fabric characteristics

Composición Composition	Poliéster HT 1100 dtex recubierto de PVC PVC coated polyester HT 1100 dtex	
Tipo de tejido Type of fabric	Impermeable translúcido Translucent waterproof	
Acabado Finish	Liso brillante lacado a 1 cara Brilliant smooth lacquered on one side	
Uso Use	Exterior Outdoor	

Características técnicas | Technical characteristics

Peso Weight	610 g/m ²	UNE-EN ISO 2286-2
Espesor Thickness	0,51 mm	UNE-EN ISO 2286-3
Ancho Width	250 / 300 cm	
Longitud de pieza Standard roll length	60 m	
Resistencia a la tracción (urdimbre/trama) Tensile strength (warp/weft)	275/265 daN/5 cm	UNE-EN ISO 13934-1
Resistencia al desgarro (urdimbre/trama) Tear strength (warp/weft)	50/30 daN/5 cm	UNE-EN ISO 4674-1
Adherencia del recubrimiento Coating adhesion	10 daN/5 cm	Método Interno basado en UNE-EN ISO 2411 Internal procedure based on UNE-EN ISO 2411
Resistencia al frío y al calor tras ensayo de tropicalización Resistance to cold and heat after tropicalisation test	-30°C / +70°C	UNE 53243-22
Solidez del color a la luz artificial - Xenotest Colour fastness to artificial light - Xenotest	4-5 (Buena-Excelente) Escala de grises 7-8 (Muy buena-Excelente) Escala de azules 4-5 (Good-Excellent) Grey scale 7-8 (Very good-Excellent) Blue scale	UNE-EN ISO 105 B02
Solidez del color a la intemperie artificial - Xenotest Colour fastness to artificial weathering - Xenotest	4-5 (Buena-Excelente) Escala de grises 4-5 (Good-Excellent) Grey scale	UNE-EN ISO 105 B04
Comportamiento en ambiente salino Performance in saline environment	Sin ampollamiento. Sin agrietamiento. Sin cambios No blistering. No cracking. No change	UNE-EN ISO 9227
Resistencia a los agentes químicos Resistance to chemical agents diluted in water	Limpiacristales, amoníaco, lejía - Sin alteraciones Alcohol - Pérdida de brillo y elasticidad Window cleaning fluid, ammonia, bleach - No change Alcohol - Loss of shine and elasticity	UNE-EN ISO 2812-1

Ventajas y beneficios | Advantages and benefits

Ancho gran formato Large wide format	Estabilidad dimensional Dimensional stability	Amplia gama de colores y acabados Wide range of colours	Tejidos aptos para impresión Printable fabrics	Fácil mantenimiento Easy to clean	Resistentes al paso del tiempo Stands the test of time

Seguridad, salud y medioambiente | Safety, health and environment


RECASENS
BCN 1886

Sistema de Gestión
ISO 9001:2015
www.tuv.com ID: 815508787


OFICINA CENTRAL / HEADQUARTERS
 Travessera de Gràcia, 18-20 - 08021 Barcelona (Spain)
 Tel./Phone: +34 932 002 700 - Fax: +34 932 021 932
 info@recasens.com - www.recasens.com

Las características técnicas indicadas son valores medios con una tolerancia de +/-5%. Los datos indicados en el presente documento son resultado de ensayos realizados en laboratorio o de cálculos técnicos conformes a las normativas vigentes. Dado que nuestros productos están en constante evolución, en base a la demanda del mercado y a los avances técnicos, S.A. RECASENS se reserva el derecho a modificar estos datos en todo momento, siendo responsabilidad del cliente verificar que los datos que está consultando corresponden a la última actualización. El cliente será responsable de la correcta utilización del tejido en lo que se refiere a las aplicaciones para las que está concebido y recomendado. S.A. RECASENS declina toda responsabilidad en lo que se refiere al montaje y puesta en obra de sus productos. Así mismo declina toda responsabilidad en cuanto a la instalación de sus productos incumpliendo las normativas vigentes. Las fotografías y descripciones de este catálogo no tienen ningún valor contractual, se indican únicamente a título orientativo. S.A. RECASENS se reserva en todo momento el derecho de hacer las modificaciones que considere oportunas. Copyright © 2022 S.A. RECASENS. Todos los derechos reservados.


The technical characteristics shown are average values with a +/-5% tolerance. The data indicated in this document are the result of laboratory tests or technical calculations in accordance with current regulations. As our products are constantly evolving, according to market demands and technical progress, S.A. RECASENS reserves the right to change these data at any time. It is the customer's responsibility to check that the data they are consulting are from the most recent update. The customer shall be responsible for the correct use of the fabric with regard to the applications for which it has been designed and recommended. S.A. RECASENS accepts no responsibility regarding the assembly and installation of its products. It also accepts no responsibility for its products being installed in non-compliance with current regulations. The photographs and descriptions in this catalogue have no contractual value, they are indicated for guidance only. S.A. RECASENS reserves the right to make any modifications it deems appropriate. Copyright © 2022 S.A. RECASENS. All rights reserved.



099 BLANCO - WHITE



099 BLANCO - WHITE
RAL 9010 - 2,5 / 3 m



005 MARFIL - IVORY
RAL 1013 - 2,5 / 3 m



004 CREMA - CREAM
RAL 1014 - 2,5 m



158 BEIGE
RAL 1001 - 2,5 / 3 m



036 AMARILLO
YELLOW
RAL 1018 - 2,5 m



555 AMARILLO OSCURO
DARK YELLOW
RAL 1003 - 2,5 m



567 QUISQUILLA
ORANGE
RAL 2004 - 2,5 m




082 ROJO OSCURO
DARK RED
RAL 3002 - 2,5 m



075 VIOLETA - VIOLET
RAL 4006 - 2,5 m



179 GRANATE
BURGUNDY
RAL 3005 - 2,5 m



156 MARRÓN
BROWN
RAL 8014 - 2,5 m



174 AZUL - BLUE
RAL 5015 - 2,5 / 3 m



073 AZUL EUROPA
BLUE
2,5 / 3 m



131 PISTACHO
PISTACHIO
2,5 m



165 MANZANA
APPLE
RAL 6024 - 2,5 m



166 VERDE - GREEN
RAL 6026 - 2,5 m



095 GRIS CLARO
LIGHT GREY
RAL 7038 - 2,5 m



096 GRIS OSCURO
DARK GREY
RAL 7037 - 2,5 m



090 NEGRO - BLACK
RAL 9005 - 2,5 / 3 m



Star Plus

Membranas impermeables y versátiles para protección solar. Son tejidos translúcidos, lacados a una cara, elaborados a partir de hilo de poliéster de alta tenacidad recubiertos de PVC.

Waterproof, versatile membranes for sun protection. These are translucent fabrics, lacquered on one side, made from high tenacity polyester yarn and coated with PVC.

Propiedades | Properties




Impermeabilidad total
Fully waterproof



Translucidez
Translucent



Confort térmico
Thermal comfort



Resistencia al moho, bacterias y hongos
Resistance to mould, bacteria and fungi

Aplicaciones | Applications

