



Grinding machine for complete machining of rotary tools with maximum flexibility





////// ROTARY TOOLS

DOUBLE SPINDLES FOR HIGH EFFICIENCY.

The VGrind 260 has everything you could possibly need for completely machining your rotary tools. Ideal for sectors such as the automotive engineering, tool making, medical technology, precision engineering and aerospace industries, as well as many more.

The VGrind 260 is equipped with tried-and-tested kinematics and a double spindle. Get ready for outstandingly precise multi-layer machining. And the best thing about it? You can configure the VGrind 260 to meet your precise requirements.

From automating to coolant distribution to configuring the spindles and much, much more - assemble your machine so that it works exactly how you need it to. The VGrind 260 offers a wealth of corresponding options.



1 ///// MODERN OPERATING CONCEPT

Height-adjustable, with touch screen, 19" diagonal screen size and optimum view into the machining chambers.

2 ///// WALL CONCEPT

Very rigid, compact construction with optimal accessibility and overview for the operator.

5 ////// NUMROTOplus®

The reliable, intuitively operated software with 3D tool and machine simulation, combined with collision monitoring.

3 ////// MULTI-LAYER MACHINING

Two vertical grinding spindles with the grinding wheel at the C axis pivot point. Reduced machining times thanks to shorter linear-axis travel distances.

6 ////// GRINDING WHEEL CHANGER

Provides even more flexibility in your manufacturing processes - with up to eight grinding wheel packages.


4 ///// INCLUDES IOT GATEWAY

The hot topic of Industry 4.0: Our machines are ready to communicate. An IoT gateway, which enables central machine data acquisition, is installed as standard.

7 ////// AUTOMATION

The VOLLMER HP 160 pallet magazine, the HC 4 chain magazine, or the internal pallet loader automatically ensures increased capacity and flexibility.

// THE MACHINE CONCEPT



////// GRINDING WHEEL PACKAGES sit at the C axis pivot point

Precision and efficiency squared: This principle is also followed by the **V**Grind 260 – thanks to two vertically configured grinding spindles. Its efficient cooling concept has been optimised. The result: Maximum perfection at the lowest tolerances with the best possible cooling.

/// Five-axis CNC grinding machine with innovative kinematics

/// Two grinding spindles situated one above the other with the grinding wheels positioned at the C axis pivot point – to ensure extremely precise grinding results

/// The two vertically positioned grinding spindles eliminate previous issues with the floating bearing compared to a single spindle with two ends



/////// DOUBLE SPINDLE for extremely precise grinding results

/// Innovative wall concept with the highest possible rigidity and outstanding damping thanks to polymer concrete

/// The plate heat exchanger on the **V**Grind 260 guarantees effective, long-term cooling for the motors and grinding spindles.

Even better - no additional cooling unit is required

/// Both grinding spindles can be fitted with various different grinding wheel packages.

The automation option ensures seamless grinding wheel replacement, every time



////// WHEEL MEASURING PROBE
Grinding wheel measurements
and wear control

// THE MACHINE CONCEPT

OPTIONAL EQUIPMENT

/// Flexible automation options for rotary tools

/// Grinding spindle available with direct or belt drive

/// Automatic changing of grinding wheel sets complete with coolant nozzles for optimum productivity



////// GRIPPER COMPENSATION
Safe, precise loading and unloading





////// ROUGHING UNIT for opening the abrasive coating

/// The automatic handling mechanism compensation during the process ensures maximum precision when loading and unloading tools and reduction sleeves.

This reduces wear and optimises concentricity

/// Wheel measuring probe: Grinding wheel measurements and wear control within the machine

/// Automated changing of intermediate sleeves with bayonet

/// Automatic roughing unit enables the grinding wheel coating to be opened during production

/// Simultaneous grinding wheel package and tool change in combination with the HP 160 pallet magazine or the HC 4 shortens non-productive times during loading

/// Stable, fully adjustable steady rest with automatic stroke ensures optimal grinding results



////// STEADY REST WITH AUTOMATIC STROKE ensures an optimal grinding result for longer tools

MAXIMUM PRECISION

////// For complete machining of tools.





For diameters up to 200 mm*

// THE OPERATING CONCEPT

Thanks to its simple, intuitive operation, the **V**Grind 260 ensures that you always have everything under control. The height-adjustable control desk, which features a clear LCD display, is positioned so that you always have a good view of the work area. During operation, you can choose to use the keyboard, touch screen or both – whichever is right for you.

The manual operating unit ensures even more flexibility: It can be freely positioned on the enclosure and is designed for setting individual axes – without using the control panel.

In short, the **V**Grind 260 has been optimally designed with ergonomics and intuitive operation in mind – for your benefit. It makes it easy for you to achieve the best possible results.



////// ERGONOMIC OPERATION

Flexible, height-adjustable and tilting control desk, versatile manual operating unit, optimal view of the machine, simple access to the grinding spindles. It doesn't get more flexible than this.



////// RELIABLE SOFTWARE SYSTEM NUMROTOplus®

// NUMROTOPLUS® SOFTWARE

VOLLMER consciously opted for a well known system that is already established on the market. The logically structured interface guarantees intuitive handling. With established programming systems, a huge variety of tools can be manufactured and resharpened. You can change any detail of your tools and adapt them to your individual requirements.

Fully informed: Thanks to a perfect 3D simulation of the tool and machine. And with collision monitoring, you can always stay on the safe side.

```
/// Develop
```


/// Simulate

/// Monitor


/// Produce

/// Measure
/// Resharpen

/// Document




////// PROGRAMMING of various tools



////// TOOL AUTOMATION thanks to a range of automation options

// AUTOMATION

Work process automation is one of the key factors of modern tool machining. With the **V**Grind 260, you can choose from a range of excellent equipment options. This allows you to implement different batch sizes for your tools and to make your manufacturing processes quicker, safer and more precise.



////// HP 160 PALLET MAGAZINE for quickly supplying up to 900 blanks or tools


// TOOL AUTOMATION

The various automation options that we offer enable you to optimally adjust the **V***Grind* 260 to your requirements.


/// HP 160 pallet magazine with compact pallets (for up to 900 blanks or tools) and double gripper to guarantee quick changing times

/// The HC 4 chain magazine has space for 158 shank-type tools or, alternatively, up to 39 HSK-A63 tool holders in a compact design

/// Also available with an internal pallet loader. This provides space for two compact pallets with a capacity of up to 300 blanks or tools. Alternatively, chaotic loading of different shank diameters is also possible



////// THE HC 4 CHAIN MAGAZINE for 158 shank-type tools or up to 39 HSK-A63 tool holders



////// INTERNAL PALLET LOADER with space for up to 300 blanks or tools


// AUTOMATION

With the eight-tool grinding wheel changer, you automatically have the right grinding wheel on hand. If required, this can also include interchangeable coolant elements on both grinding spindles. This helps to increase productivity in your manufacturing facility.

The oriented spindle holder automatically positions the new grinding wheel packages in the same location on the grinding spindle. This reduces planing and run-out errors and therefore increases precision.



////// EIGHT-TOOL GRINDING WHEEL CHANGER for efficient grinding wheel replacement and reduction in non-productive time



////// EIGHT-TOOL GRINDING WHEEL CHANGER including interchangeable coolant elements

// SPECIFICATIONS


GRINDING WHEEL


GRINDING SPINDLES

	Belt spindle	Belt spindle	Motor spind
Speed	10,500 rpm	6500 rpm	16,000 rpm
Drive output 100% duty cycle	11 kW	5 kW	10 kW
Peak power	23 kW	9 kW	20 kW
Torque	14 Nm	7 Nm	9.5 Nm
Spindle adaption	HSK50***	HSK50***	HSK50***

TRAVERSE RANGES

X1 axis	425 mm
Y1 axis	490 mm
Z1 axis	500 mm
A1 axis	360°, 450 rpm
	Optionally 1000 rpm
C1 axis	+15° to -200°
CONNECTED LOAD	Approx. 18 kVA
WEIGHT	Approx. 4900 kg net
WEIGHT	Approx. 4500 kg net





^{*} Depending on the equipping, the machine kinematics also allow for larger diameters.

** From the front edge of the workpiece carrier without measuring the cooling channel.

*** Max. 125 mm with supporting device.

**** Up to three grinding wheels per spindle end.



V@dison:

DIGITAL SOLUTIONS – PRECISION IN TRANSFORMATION
Do you want to optimise your processes with smart technologies, avoid mistakes and reduce downtimes? We offer grinding and sharpening machines that are equipped with an IoT gateway as standard. Contact your VOLLMER representative or find out

www.vollmer-group.com/en/products/digitalisation

VGrind 260 – THE MAIN ADVANTAGES AT A GLANCE:

Innovative kinematics with multi-laye machining for maximum quality of results. Benefit from uncompromising

/// INCREASED EFFICIENCY
Shorter non-productive times thanks
to intelligent and flexible automation.

/// INCREASED USER CONVENIENCE Good accessibility, ergonomically operated control panel and reliable software. Make your work easier.

/// INCREASED FLEXIBILITY Efficiently machine tools with different diameters. For precision in the format of your choice.

315/en/800/04.22/Holzer

